1011001 1101	
UHKDU/PRO/SOGE/SVS/0524 /2020	
	UNIVERSITY HOSPITAL General Sir John Kotelawala Defence University
•••••	

University Hospital Kotelawala Defence University Werahara ,Boralesgamuwa

Sri Lanka

T:Phone: 0112044555 Fax: 0112044592

Web:

21 / 06 / 2023.

INVITATION TO BID AND GENERAL CONDITIONS OF TENDER

- 1. The Vice Chancellor of the General Sir John Kotelawala Defence University, as the Chairman, Department Procurement Committee invites Bid/s from prospective Bidders for sewage treatment plants Course & rescue training programme
- 2. <u>CLOSING DATE & TIME</u>. The tender will close at 1400 hrs on 05/07/2023 Any Bid submitted after the closing time of the tender will be rejected & unopened such bids will be returned to the bidder.
- 3. <u>VALIDITY OF BID.</u> The bid submitted under this tender <u>must be valid for a period of 120 days from the date of closing of tender.</u>
- 4. **BID BOND / GUARANTEE.**

Tender No:

- (b) Submission of insufficient Bid Bond/Guarantee value or period will be considered as a "**major deviation**" and such offer will not be considered for further procurement action and will be rejected.
- 5. **VALUE ADDED TAX.** The Bidders who bid for locally delivered items must have the VAT registration. The VAT portion must be shown separately in the price schedule in Annex "A" and VAT registration number must be indicated. If the quoted item is exempted from VAT or Bidding Company is not liable for VAT, reference number and date of relevant Act number/Gazette notification/a certificate (as applicable) **issued for the current financial year** from the Commissioner General of Inland Revenue to that effect should be submitted along with the Bid.
- 6. **BID SUBMISSION.** The bidder must duly sign at the last page (before Annexes) of this document indicating the name of the signatory and the name of the company & place the company common seal to confirm the acceptance of tender conditions. The Bid/s that do not include authorized signature will be rejected. The Bid/s duly signed by the bidder enclosed and sealed in an appropriate cover addressed to the following address should be sent by registered post or could be deposited in the appropriate tender box placed at University Hospital Kotelawala Defence University, Werahara (at the Main Entrance of University Hospital Kotelawala Defence University) on or before the time & date specified for the closing of tender. The tender reference number, date & time of closing tender should be indicated & underlined at the top left corner of the envelop.

- 7. The Bid/s must be submitted in the attached schedule of prices in Annex "A" as applicable. However, bidders could use similar formats prepared with their own letter heads with all the details mentioned therein and submit in three copies along with duly signed copy of a General Conditions of tender. The Bid/s must contain Technical Literature, Pamphlets, Drawings and Quality Standard Certificate etc necessary to determine characteristics of items offered and in case of Machinery/Vehicles & Equipment, servicing and workshop data/after sales service, back up facilities or any other facilities provided by the supplier.
- 8. <u>SUBMISSION OF SAMPLES/PAYMENT OF TESTING CHARGES</u>.

When it is required to submit samples, <u>every offer</u> must be accompanied with pre - marked samples. The marking of samples <u>indicating the Bidder & Offer number</u> must be done and the samples must be handed over to the officer at same place where tender box is placed <u>on or before the closing date & time of the Bid</u>. Samples submitted after closing time of the Bid will be rejected. The documents such as Air Way Bills etc, will not be accepted in place of samples. When the testing charges are required to be paid, bidders shall pay testing charges separately <u>for all offers</u> indicated in their bid/s.

(1) Samples. Please submit samples.

- (2) Testing Charges. A sum of Rs. per offer must be paid to the Bursar of KDU, prior to the submission of bid and a copy of the receipt must be annexed to the bid. It is the responsibility of bidder to inform the Cashier of the Account Office to note the tender number on the receipt issued for such payments.
- 8. **BID OPENING.** All duly received bids **will be opened immediately after the scheduled closing time of Bids at the same venue**. Bidders or their accredited agents could be present at the time of opening of bids.
- 9. PRICES.

For locally delivered items (including locally manufactured items & foreign items imported by the bidders) price must be quoted in Sri Lankan Rupees, inclusive of all charges for delivery of items to University Hospital General Sir John Kotelawala Defence University Werahara, <u>Unit price. VAT and Total price should be clearly indicated in schedule in Annex "A"</u>. Other than VAT, all other type of taxes (eg: NBT, BTT, etc.) should not be indicated separately and should be included in unit price.

10. **RESTRICTED TENDERS**. Invitation to Bids are circulated among the registered suppliers with Ministry of Defence (MOD), only bids submitted by registered suppliers will be allowed for consideration. However, Chairman, Department Procurement Committee reserves the right to invite the bids from multiple combinations of Procurement Methods as stipulated in Chapter III of the Government Procurement Guideline, 2006 to ensure highest competitiveness.

- 11. **PERFORMANCE BOND/GUARANTEE.** A successful bidder shall furnish a Performance Bond/Guarantee in the form of "On Demand" & "Unconditional" Bank/Insurance Guarantee for a sum equivalent to 10% of the contract value for every contract that exceeds Rs. 2,000,000.00 or equivalent amount in foreign currency through a recognized Commercial Bank registered in Sri Lanka or through an Insurance Company authorized by the Insurance Board of loss resulting from the supplier's failure to complete his performance obligations under the contract. If the contracted supplier fails to deliver the items Sri Lanka to issue such Performance Guarantee for this purpose, **within two weeks from the date of notification of award**. The proceeds of the Performance Bond/Guarantee shall be payable to the Vice Chancellor of the General Sir John Kotelawala Defence University as compensation for any o
- 12. time or fails to complete the works as per the agreed contract, **THE TOTAL VALUE OF THE PERFORMANCE BOND/GUARANTEE** will be forfeited. If only partial delivery is made during the agreed contract period, the corresponding value percentage of undelivered quantity from the Performance Bond/Guarantee will be forfeited.
- 13. SIGNING OF CONTRACT. The notification of award will be transmitted to the successful bidder by post, by fax or email. This notification constitutes the formation of the contract. The successful bidder should submit his written acceptance for the award and performance bond / guarantee (For awards over Rs. 500,000.00 without VAT) within 14 days of receipt of such notification. Upon acceptance of the award and furnishing of the Performance Bond/Guarantee, the successful bidder will have to enter into a formal contract with the Vice Chancellor of the General Sir John Kotelawala Defence University by signing the Contract.
- 14. **DELIVERY.** Preference will be given for early delivery. In case of bulk supplies for locally manufactured items, the delivery of **total quantity must be completed within 120 days of signing of contract**, unless mutually agreed for extended delivery period with University Hospital Kotelawala Defence University. **The bidder/s must indicate the proposed delivery schedule in Annex "E"**. In the event of placing a purchase order with the successful bidder, the total quantity so ordered must be supplied as one consignment unless part deliveries are agreed upon in the contract. The deliveries not made as per agreed delivery schedule will be considered as bad performances by the suppliers and **no extended delivery period will be authorized**. Under extreme unavoidable conditions too, the Chairman, Department Procurement Committee (Vice Chancellor of the General Sir John Kotelawala Defence University) reserves the right to grant or refuse delivery period extensions only within the current financial year with or without liquidated claim for delayed deliveries and that decision will be final.
- 15. **LIOUIDATED DAMAGES.** In case of delivery period extensions requested by the successful bidder, a sum equivalent to 2% of the total value of the delayed supply per delay of one week or part thereof may be deducted from the payment due to the supplier from the University Hospital General Sir John Kotelawala Defence University as liquidated damages up to the maximum limit of 10% of the total value of delayed supplies.
- 16. PAYMENT TERMS FOR LOCALLY DELIVERED ITEMS. Payment will be made after acceptance of items which should be subjected to a pre-acceptance inspection/testing by University Hospital General Sir John Kotelawala Defence University authorities. The delivery made to University Hospital should not be considered as quantities taken over by University Hospital General Sir John Kotelawala Defence University until items are properly accepted after pre-acceptance inspection. Any item that does not conform to the specifications or already approved sample will be rejected & it is the responsibility of the supplier to remove them from University Hospital stores/premises within 07 working days of such intimation (either verbal or written) at his own cost and replace them with items conforming to specification within one month of such rejection. The bidder shall allow approximately 60-90 days period of credit from the date of acceptance of items for Account Office, University Hospital General Sir John Kotelawala Defence University to obtain liquid cash from General Treasury & release the payment.
- 16. **RIGHTS OF THE PROCUREMENT COMMITTEE**. The Department Procurement Committee reserve the right to accept or reject whole or part of this tender and their decision will be final. The successful bidders will be notified. Information with regard to rejected or unsuccessful bids will not be communicated.

 Thanking You,

JMSR Yayawardana
Lieutenant Commander (S)
PROCUREMENT MANAGER
For Vice Chancellor

University Hospital Kotelawala Defence University

I/We agree to abide by the conditions of tender and undertake to supply the items as per delivery schedule mentioned in the contract, in the event of an order been placed with me/my firm/company as a result of this tender.

Signature

Name of Signatory

FILE NO - UHKDU/PRO/SOGE/SVS/0524/2020

SCHEDULE OF PRICES FOR LOCALLY DELIVERED ITEMS

S/N	ITEMS	UNIT	QTY	PRICE EACH SLRS	TOTAL PRICE SLRS
	Design, Fabrication & Build of Soundproof Audiology Room Of ENT				
	Specification is attached here with Annex "B"				
	TOTAL				
	DISCOUNT				
	TOTAL(AFTER DISCOUNT)				
	VAT %				
	GRAND TOTAL				

2.	a . Validity	: 120 days from the date of closing of tender
	b . Payment term	: Credit
	c .Warranty	:
	d . Brand name	:
	e .Country of origi	:
3.	VAT Registration No. : .	
4.	Name of the Company	
5.		: Rs
6.	Signature of Bidder :	
7.	Date. :.	
8.	MOD registered No :.	Company Seal:

PROCUREMENT MANAGER
University Hospital
General Sir John Kotelaniala Delenge University
Werathera

1. Project

Settling up a professional Audiometric suite for ENT Department of University Hospital of KDU, for conducting Diagnostic tests for patients with hearing impairments and related issues.

2. Scope

proposed by the ENT Consultant of UHKDU, soundproofing and final finishes to comply with professional standards. The scope of the project involves re-configuration of the room layout in the allocated space in the existing building, as per the new room layout

Proposed Audiometric suite comprises of three sound proof functional modules.

-) Audiometric Booth (Patient's Room)
- Control Room (Audiologist's room)
- Audiology Room (ABR room)

2.1 Scope of the document

of the three functional modules. This specification addresses the needs of stipulation of standards for the setting up of the aforementioned Audiometric suite comprising

3. Technical Specifications

Audiometric Booth 1. Noise level < 34 dB
Voise level < 34 dB

PROCUREMENT MANAGER
University Hospital
General Sur John Kotelanisia Delence University
Werathera

be less than 34 dB with Air-conditioning system switched "on." All structure borne vibrations shall be eliminated through means of isolation Double wall construction shall be used where necessary & applicable. Refer to table 1. below for details of NR characteristics. Bund Absorption level – Material Average RC > 0.9 Internal sound absorption shall be at or better than the levels given in the table 2. at respective frequencies indicated. Any acoustically hard surfaces shall be lined with absorbent layers in order to minimize sound reflection. Reverberation time < 0.25 seconds. Construction Construction Construction of masonry walls, during the re-configuration of current room layout, shall be carried out using the same types of material as in the existing construction. (Concreta, Cement blocks, Bricks etc.) but no subst tutes. Inner walls shall be treated with acoustically absorbent material of which NRC>0.9 (2-inch thickness rock wool, glass wool etc. on wooden frames etc.) to
In the the control of

PROCURED OF MANAGER
University Hospital
Geograf Sur John Kotelaniata Delence University
Werathera

2 0																			
	and City of Street City of Street			The state of the s												The County of the Sales of the County of the		THE SECOND SECON	
tions shall be , to minimize		ed from the	r to make it a	uld be	with circular couplings.	s should be	absorbent layers	hes. uctions shall be	, to minimize			ly isolated from	be installed.	oor (Excluding	bear the weight), in case of	JKg / sq foot.	ly to absorb	tc).
Asymmetric wall constructions shall be applied, where necessary, to minimize Reverberation time	Roof (Ceiling) construction	A secondary ceiling, Isolated from the	walls of the booth in order to make it a	Air conditioning ducts should be	terminated at this ceiling, with circular diffusors through flexible couplings.	Inner surface of the ceiling should be	acoustically treated with absorbent layers	and appropriate final finishes. Asymmetric ceiling constructions shall be	applied, where necessary, to minimize	Reverberation time.	Floor construction	A floating floor, acoustically isolated from	the structural floor, shall be installed.	I hickness > 25mm solid floor (Excluding re-enforcement frame, if any)	Shall be strong enough to bear the weight	of inner walls of the booth, in case of double wall construction.	Load bearing capacity > 50Kg / sq foot.	Shall be treated acoustically to absorb	(Carpeting, under layers etc).
≡	4.	:		⊭		≡		. <u>></u>			5. FI		:	≓	iii iii		ïv.	>	

	Door	and the experience	Town Shitangers	
	Shall be Sound proof, single leaf and flush mounted to the wall with frame.			
:	Material - Steel (GI coated and spray			
	painted or powder coated).			
:=:	STC Rating >50	The rest of the state of the st		
i≡	Dimensions of D2 - 7' (H) \times 3' (W) \times 2.5"	STEEL		
	(D).		A CONTRACTOR OF THE	
iv.	Acoustically treated to be sound proof and			
	absorptive.			
``	Shall be anchored with heavy duty, offset			
	pivoted, cam-lift hinges (self closing).			
vi.	Fitted with Dual line Neoprene / EPDM			
	Rubber compression beading on the			
	perimeter for sound proofing (all four			
	sides).			
vii.	Bottom sill - Stainless Steel plate			
	compressed.			
viii.	Tower Bolt type latches (Stainless Steel).			
×.	Stainless Steel Push Plates & Pull handles.			
×	Dual layer glass Vision Panel.			
×i.	Modular fabrication of Door & Frame.			
7. \	Window - (To control room)			
	Condensation free Double Glazed unit (DGU) glass window with 6mm glasses		The water of the seal	
	Hermetically sealed.	2008 SE 5008	Applied the State of the	
≔	Encapsulated in Aluminum / GI Frame		and the second second	
ii	Dimensions 4' (W) ×3' (H)			
i×.	STC > 45			
``	Desiccator material included in the gap.			

PROCURED OF MANAGER
University Hospital
Geograf Str. John Kotelanista Defence University
Werathera

8. Temperature i. Adjustable - between 20 – 27 degrees ii. See note 1 below. iii. See note 2 below. iii. See note 2 below. iv. Controller mechanisms / Electronics shall be installed for the same. 9. Illumination ii. Minimum Light level - 800 Lux , Inside at 30" height level from the floor of the booth. Colour Temperature >6000 K (Cool white) iii. Colour Temperature >6000 K (Cool white) iii. PFI free LED lighting. iv. 02 lighting fixtures (ceiling mounted), Flicker-free, even distribution with diffused light. v. Pre wired individual switches with RFI-free Dimmers. 10. Speaker mounts 10. Speaker mounts 10. Speaker mounts (02 Nos.) - Acoustically isolated from the floor, walls or ceiling. iii. Urrical pole type speaker mounts (02 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) iii. Height adjustable along the vertical pole iv. Pre-wired speaker points 11. Interface connector / jack / patch panel	Temperature Adjustable - between 20 – 27 degrees Centigrade. See note 1 below. See note 2 below. Controller mechanisms / Electronics shall be installed for the same. Illumination Minimum Light level - 800 Lux , Inside at 30" height level from the floor of the booth. Colour Temperature > 6000 K (Cool white) RFI free LED lighting. O2 lighting fixtures (ceiling mounted), Hicker-free, even distribution with diffused light. Pre wired individual switches with RFI-free Dimmers. D. Speaker mounts Vertical pole type speaker mounts (02 Nos.) – Acoustically isolated from the floor, walls or ceiling. O2 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) Height adjustable along the vertical pole v. Pre-wired speaker points 11. Interface connector / jack /patch panel						
Temperature Adjustable - between 20 – 27 degrees Centigrade. See note 1 below. See note 2 below. Controller mechanisms / Electronics shall be installed for the same. Illumination Minimum Light level - 800 Lux , Inside at 30" height level from the floor of the booth. Colour Temperature >6000 K (Cool white) RFI free LED lighting. 02 lighting fixtures (ceiling mounted), Flicker-free, even distribution with diffused light. Pre wired individual switches with RFI-free Dimmers. Speaker mounts Vertical pole type spéaker mounts (02 Nos.) – Acoustically isolated from the floor, walls or ceiling. 02 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) Height adjustable along the vertical pole Pre-wired speaker points Interface connector / Jack / patch panel	Temperature Adjustable - between 20 – 27 degrees Centigrade. See note 1 below. See note 2 below. Controller mechanisms / Electronics shall be installed for the same. Illumination Minimum Light level - 800 Lux , Inside at 30" height level from the floor of the booth. Colour Temperature >6000 K (Cool white) RFI free LED lighting. 02 lighting fixtures (ceiling mounted), Flicker-free, even distribution with diffused light. Pre wired individual switches with RFI-free Dimmers. Speaker mounts Vertical pole type speaker mounts (02 Nos.) – Acoustically isolated from the floor, walls or ceiling. 02 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) Height adjustable along the vertical pole Pre-wired speaker points Interface connector / jack / patch panel	11. iv.	:	-	10.		≤ .
		. Int		Vertical pole type speaker mounts (02 Nos.) – Acoustically isolated from the		Adjustable - between 20 – 27 degrees Centigrade. See note 1 below. See note 2 below. Controller mechanisms / Electronics shall be installed for the same. Illumination Minimum Light level - 800 Lux , Inside at 30" height level from the floor of the booth. Colour Temperature >6000 K (Cool white) RFI free LED lighting. 02 lighting fixtures (ceiling mounted), Flicker-free, even distribution with diffused light. Pre wired individual switches with RFI-free Dimmers.	Flexible coupling for the air gap (wiiii. 4).

PROCURE STATE MANAGER
Unwersity Hospital
General Sur John Kotelaniala Delence University
Werahera

		3
4 - = =	<u>ξ</u>	2. ∷
Roof (Ceiling) An acoustically treated ceiling shall be installed to achieve stipulated noise and absorption conditions, reverberation times. Air conditioning ducts should be terminated at this ceiling, with circular diffusors through flexible coupling. A secondary ceiling shall be installed, in case if the stipulated conditions cannot	Internal sound absorption shall be at an average level of 0.6 or more. Any acoustically hard surfaces shall be lined with absorbing layer in order to minimize sound reflection. Wall construction Construction of masonry walls, during the re-configuration of the room layout, shall be carried out using same types of material as in the existing construction (Concrete, Cement blocks, Bricks etc.) but no substitutes. Inner walls shall be treated with acoustically absorbent material and a top final finish layer.	room shall be less than 40 dB with Air conditioning system switched "on". All structure borne vibrations shall be eliminated through means of isolation or absorption. Sound Absorption level – Material Average
	Q.	
		< < < < < < < < < < < < < < < < < < <

PROCURTER OF MANAGER
University Hospital
Geograf Str. John Kotelanista Delence University
Werathera

PROCURE BY MANAGER
University Hospital
General Sur John Ketelawaia Delence University
Werathera

iv. If a second ceiling is installed, Air conditioning ducts should be terminated at the second ceiling, with circular diffusors through flexible couplings. v. Inner surface of the ceiling should be acoustically treated with absorbent	S. Floor i. Existing floor shall be treated acoustically to absorb Structure borne low frequency vibrations, sound and minimize foot step noise (carpeting, under layers etc.).	 6. Doors i. Shall be Sound proof, single leaf and flush mounted to the wall with frame. i. Material - Steel (GI coated, Spray painted or Powder coated). ii. STC Rating >50 iii. Dimensions of D2 - 7' (H) x 3' (W) x 2.5" (D). iv. Acoustically treated to be sound proof and absorptive. 	v. Shall be anchored with heavy duty, offset pivoted, cam-lift hinges (self closing). vi. Fitted with Dual line Neoprene / EPDM Rubber compression beading on the perimeter for sound proofing (all four sides). vii. Bottom sill - Stainless Steel plate compressed.



≡ = %	≤. ≣: ⊨: ∟. ∞		7. X. X. X. X. X.
Illumination Minimum Light level - 800 Lux - Inside at 30" height level of the booth. Colour Temperature > 6000 K (Cool white) 04 lighting fixtures (ceiling mounted), Flicker-free, even distribution with	Temperature Adjustable between 20 – 27 degrees Centigrade. See note 1 below. See note 2 below. Controller mechanisms / Electronics shall be installed for the same.	Double glazed window to the Audiometric booth. Condensation free Double Glazed unit (DGU) glass window with 6mm glasses Hermetically sealed. Encapsulated in Aluminum / GI Frame. Dimensions 4' (W) x 3' (H) STC > 45 Desiccator material included in the gap Flexible coupling for the air gap (Min. 4").	Key lock type latches (Stainless Steel). Stainless Steel Push Plates & Pull handles. Dual layer glass Vision Panel. Modular fabrication of Door & Frame. Window — (to Audiometric booth) This refers to a part of the item given above under Audiometric booth (item 6).
18 8 8 B			

PROCURTER OF MANAGER
University Hospital
General Str. John Kotelanista Delence University
Werahera

Speaker mounts Speaker mounts Con Nos. Swivel mounts with Three DOF (comparities (row floor , wall and ceiling. Pre-wired speaker points Interface connector/jack/patch panel A Flush mount metallic patch panel shall be installed below the window to the Audiometric booth. It shall contain, 2-pin Speaker sockets - 04 nos. 9-pin D socket - 01 No. BNC sockets - 02 nos. 9-pin D socket - 01 No. BNC sockets - 02 nos. 1-pin Speaker - 03 nos. 1-pin Speaker - 04 nos. 1-pin Speaker - 05 nos. 1-pin Speaker - 04 nos. 1-pin Speaker - 04 nos. 1-pin Speaker - 04 nos. 1-pin Speaker - 05 nos. 1-p			PROCU Unwersit Geograf S Weraher	N NOTE	Kotolia	sieda De		Ons.	vė/s										
circuit) with RFI-free dimmers. Speaker mounts O2 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) – Acoustically isolated from floor, wall and ceiling. Pre-wired speaker points Interface connector/jack/patch panel A Flush mount metallic patch panel shall be installed below the window to the Audiometric booth. It shall contain, 3-pin Standard ¼" Phone sockets - 04 nos. USB sockets - 02 nos. 9-pin D socket - 01 No. BNC sockets - 02 nos. 2-pin Speaker sockets - 02 nos. These connectors shall be connected to a similar patch panel (via one-to-one trunk lines), to be installed on the other side of the same wall, in the Audiometric booth specifications". Metallic plate shall be connected to system ground. Electrical outlets 13 Amp Square pin (with ground) outlets - 04Nos below the Interface jack panel,																			
	circuit) with RFI-free dimmers.	Speaker mounts 02 Nos. Swivel mounts with Three DOF (compatible with the weight of speaker) –	Acoustically isolated from floor , wall and ceiling.	Interface connector/jack/patch panel	A Flush mount metallic patch panel shall be installed below the window to the	Audiometric booth.	3-pin Standard ½" Phone sockets - 04 nos.	9-pin D socket - 01 No.	BNC sockets - 02 nos.	2-pin Speaker sockets - 02 nos. These connectors shall be connected to a	similar patch panel (via one-to-one trunk	the same wall, in the Audiometric booth	(Patient's room)- Refer "item 11" under	"Audiometric booth specifications".	Metallic plate shall be connected to	system ground.	Electrical outlets	13 Amp Square pin (with ground) outlets –	04NOS Delow the Interface Jack parier,

				-		3
					з	
 Floor Existing floor shall be treated acoustically to absorb Low-Frequency vibrations, 	 Ceiling Primary ceiling shall be acoustically treated to maintain the required absorption level. 	3. Wall Construction i. Inner walls shall be treated with acoustically absorbent foam backed fabric layer. ii. Maximum thickness shall not exceed 1"	2. Sound Absorption level - Material average>	Noise level < 40 dB Ambient noise level inside the control room shall be less than 40 dB with Air conditioning system switched "on".	Audiology Room (ABR room)	13. Accessories – Hanger Bar i. A horizontal hanger bar for patch cables, headphones etc. on the wall, mounted on to the left hand side of the patch panel – with provision of adequate space for the control desk.
			and the state of t	Although penty of the		

PROCUREMENT MANAGER
University Hospital
General Str. John Kotelsmids Defence University
Werathera

	nd flush		x 2.5"	roof	,, offset	ng).	PDM	for	The state of the s		eel).	andles.		me.		all pulition forst.
6. Door	Shall be sound proof , single leaf and flush mounted to the wall.	STC Rating >50	(D).	iv. Acoustically treated to be sound proof and absorptive.	v. Shall be anchored with heavy duty, offset		vi. Fitted with Dual line Neoprene / EPDM	Rubber beading on the perimeter for sound proofing (all four sides).	vii. Bottom sill - Stainless Steel plate	compressed.	viii. Key lock type latches (Stainless Stee	ix. Stainless Steel Push Plates & Pull ha	x. Dual layer glass Vision Panel.	xi. Modular fabrication of Door & Frame.	7. Temperatura i. Adiustable between 20 – 27 degrees	ii. See not: 1 below.

PROCUREST OF MANAGER
University Hospital
Geograf Sur John Kotolomials Delunce University
Werathera

8. Illumination i. Minimum light level - 800 Lux - Inside at 30" height level from the floor of the booth. ii. Colour Temperature > 6000 K (Cool white). iii. 04 lighting fixtures (ceiling mounted), Flickerfree, even distribution with diffused light. iv.Pre wired, 02 switches (two fixtures per circuit) with RFI-free dimmers.	9. Electrical Outlets i. 13 Amp Square pin (with ground) outlets – 04Nos. – on the wall.	Buffer Area 1. Noise level < 45 dB	i. Ambient noise level inside the Buffer area shall be less than 45 dB. (Not critical but acts as a noise buffer for two rooms)	2. Sound absorption level i. Absorption can be at a moderate (>0.4 material average) level to suppress incoming noise through sound leakages through doors ,if any. (Not critical)	3. wall construction i. Acoustical fabric overlaid thin layer of absorbent (max ¾") on four sides of the wall.	4. Ceiling

S. (Boston)	divisional facilities of the control	Tan trigital of the	Guanagis w	9 89 196 107	De la applicación de la companya de	Sould by Bally		James Separal	ty Hose	A Kotok			Unanéo	
	E House of the Bank Cook Hills	Management of the state of the	S switches thus firmther year should be skilled	2000年19	Period State (ACID) Sportion (Sportion)			Section 1976		TO Side of make the order of the column of t	AND TO EUROPE CONTROL SECTION OF THE PROPERTY		at tabile overdage from says of	Control of the second of the s
i. Suspended acoustic panel ceiling (Mineral fiber etc.) with moderate absorption.	5. Floor	or quire under layer.	6. Door	mounted to the wall.	i. Material - Steel	iii. Dimensions of D1 - 7' (H) \times 3' (W) \times 2.5" (D) iv. Acoustically treated to be sound proof and	absorptive. v. Shall be anchored with heavy duty, offset	pivoted, pam-lift hinges (self closing). vi. Fitted with Dual line Neoprene / EPDM	Rubber bading on the perimeter for sound proofing fall four sides).	vii. Bottom si - Stainless Steel plate compressed.	viii. Key-lock type latches (Stainless Steel).	ix. Stainless Steel Pull handles. x. Modular fabrication of Door & Frame.	7. Illumination	i. 600 LUX , Even illumination.

						1	
0							
With individual switches pre-wired to control desks of respective rooms	2) Audiology room door	Installed over 1) Control room door	i. RED Warning lamps - 02 Nos.	10. Accessories	i. 13 Amp – 3-pin power outlet - 01 No.	9. Electrical Outlets	iii. 01 No. fixture (ceiling mounted) with pre wired switch on the wall.
District Control of the	See Tropic when	of the property of			Shapping Janes		
PORT OF PROPER OF		100	The Party of the P	0	THE REAL PROPERTY.	The street	
0.00		3		2 1			
		SELV stdpte state	ST STATES AND LABOR			AND THE RESERVED OF	

NR in dB 47 62 (Double wall)	vall)	NR in dB 24 30	Freq (Hz) 125 250
83		40	500
91		50	1000
99		55	2000
97		55	4000
91		55	8000

Table 1. Noise Reduction Levels at Octave Band Center Frequencies.

Attenuation	Freq (Hz)
0.49	125
0.37	250
0.83	500
0.96	1000
0.99	2000
1.0	4000
1	8000

TABLE 2. Absorption coefficients at Octave Band Center frequencies.

PROCUREMENT MANAGER
University Hospital
Geograf Str. John Kotelsmale Defence University
Werathera

Notes:

- Dimensions of the construction / fabrication shall be as per the diagrams attached in section 4. (Audiometric Suite layouts) of this document, unless otherwise specified in section 3. (Technical Specification).
- conditioning supply and refurn duct lines will be routed from the Air handler Unit (AHU) of the Central AC system of the building. CFM requirement of the AG supply to be stipulated by the bidder and a request has to be made to the building contractor. (Air Internal Building contractor will provide ducts up to the facility). 2)
- Necessary noise filters, Valves, attenuators shall be installed by the bidder to Supply and Return air ducts for maintaining specified noise levels in all three rooms, and isolation of three rooms acoustically from each other. 3
- All acoustical paneling on walls and ceilings shall be with neat, rugged, durable final finish and aesthetically pleasing appearance.
- All Electrical accessories, Luminaires, controllers, dimmers etc. shall be compatible with AC power supply voltage AC 230 Volts, 50 Hz. 2
 - Electrical system shall have provision for a Single phase central UPS input with a Change-over switch (a UPS unit placed out of the Audiology unit premises) (9
- Bidder shall ensure the fire rating of all the material used for the construction and fabrication are high and the final product is fire proof and fire safe to the highest extent. Bidder shall liaise with the fire prevention department of UHKDU for any further requirements. 1


PROCUREMENT MANAGER Unwersity Hospital General Str John Kotelaminia Dete Merathera

4. Audiometric Suite Layouts

1. Existing Layout


Dimensions – As per given in the diagram

Floor to Ceiling height: 2650 mm (8' 6")



PROCURED TO MANAGER
University Hospital
General Str. John Kotelsmints Defence University
Werathers

PROCUREMENT MANAGER
University Hospital
General Sur John Ketelamida Detence University
Werathera



AUDIOLOGIST'S ROOM
PATIENT'S ROOM
D2
D2

....6

"6-t

AUDIOLOGY ROOM

BUFFER AREA

D2

D2

10

(181)

2. Proposed New Layout

5. Warrenty, Service Agreements and Documentation

All items described in the schedule should be covered by a warranty for a period of not less than 24 calendar months from the date of successful commissioning against manufacturing defects, workmanship and all other issues

1

- 2) Technology / service manuals / operations manuals, any other technical detail should be handed over to the client at the time of commissioning
- Supply of spare parts, replaceable items/ consumables should be guaranteed for a period of 10 teats starting from the date of successful commissioning. A price list for such items over a period of 10 years from the date of installation should be made

6. General conditions for bidders

- power tools, welding gear etc. during the construction. The bidder shall implement maximum level of Fire safety conditions in order to prevent any possible fire hazard in using electricity,
- All the material (wood, any absorbent material based on biomass etc.) are to be chemically treated before the delivery to the site to prevent development of breeding grounds for harmful insects (termites etc.), and any possible termite attacks at the site in the long run.
- 3 Bidder shall take necessary precautions to minimize disturbances to the ongoing operations of UHKDU during the construction & and implement a "No disturbances to ongoing operations during construction" policy during work. fabrication work. Bidder, or any representative, can liaise with professional staff at the Audiology department of UHKDU on the same
- All electrical components and conduits shall be recessed into the wall panels, and shall be wired in GI conduits with threaded joints not exposing to the exterior in order to prevent any possible electrical fires.
- 5) Screened metal galvanized (GI) power outlets (Industrial type) should be used as recessed power outlets in areas where acoustical panels, fabric lining has been installed as a part of acoustic treatment.

PROCUREMENT MANAGER
University Hospital
General Sur John Kotelanicia Delence University

Grounding terminal of the exertical system shall be provided by the bidder for a dedicated grounding system for the Audiometry suite. (Connection of this terminal to the earth ground is the responsibility of the client - UHKDU).

The bidder should provide a certificate of sound level of separate rooms as mentioned in the specification, issued by a recognized third party accreditation body following the completion of fabrication, at the expense of the bidder, as recommended by ENT Consultant. UHKDU will not bear any cost related to this procedure.

Provisions such as access to the site, utility (electricity, water etc.) and permission for work out of office hours (night work etc. if required) are responsibility of the client, UHKDU. 8

7. Bidding conditions

sound level requested by the specification, after completion, by a 3rd party accredited institution (ITI or NERD Center) at the expense 1. Bidder should be able to show prior experience in building sound proof suits in health institutions and should be able to confirm the of the bidder, before giving QQI report.

Bidding document should include the methodology and a list of material intended to use in achieving the stipulated standards.

Bidder should provide details of the products (catalogs, brochures etc.) of the material as proof. (Preferably with diagrams and technical details)

4. The site may be inspected with prior approval of the CEO, University Hospital of KDU during week days.

Prepared & Forwarded by

Engineering Consultant

MIET (UK), MIEEE (USA), MIIESL (SL) Eng. W.A.Shanthakumara BSc, MBA, PG Dip (UOM)

6th September 2022

ANNEX "D"

SPECIMEN FORM OF BID SECURITY

company) whose				called "the Bidder") and We (na fter called "the Surety") are hel the Authority") in	
	d assigns jointly and severally			t of which sum the Bidder and the	ne Surety bind themselve
Whereas		e Tender and oth	er persons	o compete tenders in similar to	erms for the supply o
submit the same for Bid") in accordance to be undertaken b	or the consideration of the Au	thority, and the Bond shall provide se	idder propo ecurity to th	ses to submit to the Authority a a Authority that the Bidder will h	
(a)	That it shall remain in full fo	orce and effect unti	l the earlies	of	
				he date stipulated by the Author the Authority by the Bidder and	
				e Authority, the date upon which terms of the contract thereby n	
(b) receipt of	Subject to this Bond being in first written demand form the			rety shall pay the full amount sp	ecified in this Bond upor
	(i) The Bidder has wi	thdrawn his Tende	er during the	validity of this Bond, or	
	(ii) The Bidder has fa the tender within 14 days from			security to the Authority in accord of the Tender.	ordance with the terms o
	ender on the part of the Auth			orgiveness in or in respect of ne the bidder shall in any way rele	
Authority shall ret	nefit of this Bond shall not be turn the same to the Bidder. and shall be governed by the la		ne Authorit	and upon its ceasing to be in	full force and effect the
I exec	cuted as a deed on this () day of () 20 ()	
For and	on behalf of the Bidder			For and on behalf of the Surety	
Signed b	oy			Signed by	
In the ca	pacity of			In the capacity of	
and by -				and by	
In the ca	npacity of			In the capacity of	
Seal (wh	nere applicable)			Seal (where applicable)	

PROCUREMENT MANAGER
Unwersity Hospital
General Str. John Kotelanista Detence University
Werathera

DELIVERY SCHEDULE

(IT IS MANDATORY TO FILL ITEM :			
DURATION		QTY	
EX STOCK QTY (WITHIN 01	WEEK)		
01MONTH			
02 MONTHS			
03 MONTHS			
04 MONTHS			
TOTAL			
NAME OF THE BIDDER	:		
SIGNATURE OF BIDDER	:		
DATE	:		
OMPANY SEAL	:	:	

PROCURTED OF MANAGER
Unwersity Hospital
Geograf Str. John Kotelaniala Delence University
Merathera